

# Product datasheet

Specifications



Miniature circuit breaker (MCB),  
Acti9 iC60L, 4P, 4A, B curve,  
15000A (IEC/EN 60898-1), 100kA  
(IEC/EN 60947-2)

A9F93404

## Main

Device application	Distribution
Range	Acti9
Product name	Acti9 iC60
product or component type	Miniature circuit-breaker
Device short name	iC60L
poles description	4P
Number of protected poles	4
[In] rated current	4 A
Network type	AC DC
Trip unit technology	Thermal-magnetic
Curve code	B
Breaking capacity	15000 A Icn at 400 V AC 50/60 Hz conforming to EN/IEC 60898-1 70 kA Icu at 440 V AC 50/60 Hz conforming to EN/IEC 60947-2 100 kA Icu at 12...60 V AC 50/60 Hz conforming to EN/IEC 60947-2 100 kA Icu at 220...240 V AC 50/60 Hz conforming to EN/IEC 60947-2 100 kA Icu at 100...133 V AC 50/60 Hz conforming to EN/IEC 60947-2 100 kA Icu at 380...415 V AC 50/60 Hz conforming to EN/IEC 60947-2 20 kA Icu at <= 250 V DC conforming to EN/IEC 60947-2
Utilisation category	Category A conforming to EN 60947-2 Category A conforming to IEC 60947-2
Suitability for isolation	Yes conforming to EN 60898-1 Yes conforming to EN 60947-2 Yes conforming to IEC 60898-1 Yes conforming to IEC 60947-2
Standards	EN 60898-1 IEC 60898-1 IEC 60947-2 EN 60947-2

## Complementary

Network frequency	50/60 Hz
Magnetic tripping limit	4 x In +/- 20 %

<b>[Ics] rated service breaking capacity</b>	100 kA 100 % conforming to EN 60947-2 - 220...240 V AC 50/60 Hz 100 kA 100 % conforming to IEC 60947-2 - 220...240 V AC 50/60 Hz 100 kA 100 % conforming to EN 60947-2 - 380...415 V AC 50/60 Hz 70 kA 100 % conforming to EN 60947-2 - 440 V AC 50/60 Hz 100 kA 100 % conforming to IEC 60947-2 - 380...415 V AC 50/60 Hz 70 kA 100 % conforming to IEC 60947-2 - 440 V AC 50/60 Hz 100 kA 100 % conforming to EN 60947-2 - 12...133 V AC 50/60 Hz 100 kA 100 % conforming to IEC 60947-2 - 12...133 V AC 50/60 Hz 7500 A 50 % conforming to EN 60898-1 - 400 V AC 50/60 Hz 7500 A 50 % conforming to IEC 60898-1 - 400 V AC 50/60 Hz 20 kA 100 % conforming to EN 60947-2 - 180...250 V DC 20 kA 100 % conforming to IEC 60947-2 - 180...250 V DC
<b>Limitation class</b>	3 conforming to EN 60898-1 3 conforming to IEC 60898-1
<b>[Ui] rated insulation voltage</b>	500 V AC 50/60 Hz conforming to EN 60947-2 500 V AC 50/60 Hz conforming to IEC 60947-2
<b>[Uimp] rated impulse withstand voltage</b>	6 kV conforming to EN 60947-2 6 kV conforming to IEC 60947-2
<b>Contact position indicator</b>	Yes
<b>Control type</b>	Toggle
<b>local signalling</b>	Trip indicator
<b>mounting mode</b>	Fixed
<b>mounting support</b>	DIN rail
<b>Comb busbar and distribution block compatibility</b>	Top or bottom: YES
<b>9 mm pitches</b>	8
<b>Height</b>	85 mm
<b>Width</b>	72 mm
<b>Depth</b>	78.5 mm
<b>net weight</b>	0.5 kg
<b>Colour</b>	White
<b>Mechanical durability</b>	20000 cycles
<b>Electrical durability</b>	10000 cycles
<b>Connections - terminals</b>	Single terminal (top or bottom) 1...25 mm <sup>2</sup> rigid Single terminal (top or bottom) 1...16 mm <sup>2</sup> flexible
<b>Wire stripping length</b>	14 mm for top or bottom connection
<b>Tightening torque</b>	2 N.m top or bottom
<b>Earth-leakage protection</b>	Separate block

## Environment

<b>IP degree of protection</b>	IP20 conforming to IEC 60529 IP20 conforming to EN 60529
<b>Pollution degree</b>	3 conforming to EN 60947-2 3 conforming to IEC 60947-2
<b>Overvoltage category</b>	IV
<b>Tropicalisation</b>	2 conforming to IEC 60068-1
<b>Relative humidity</b>	95 % at 55 °C
<b>Operating altitude</b>	0...2000 m
<b>Ambient air temperature for operation</b>	-35...70 °C
<b>Ambient air temperature for storage</b>	-40...85 °C

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	7.000 cm
Package 1 Width	7.300 cm
Package 1 Length	9.300 cm
Package 1 Weight	442.000 g
Unit Type of Package 2	BB1
Number of Units in Package 2	3
Package 2 Height	8.400 cm
Package 2 Width	10.400 cm
Package 2 Length	22.900 cm
Package 2 Weight	1.386 kg

## Contractual warranty

Warranty	18 months
----------	-----------

## Sustainability

**Green Premium™ label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency RoHS/REACH

## Well-being performance

Mercury Free

Rohs Exemption Information Yes

Halogen Free Product

## Certifications & Standards

**Reach Regulation** [REACH Declaration](#)

**Eu Rohs Directive** Compliant with Exemptions

**China Rohs Regulation** [China RoHS declaration](#)  
Product out of China RoHS scope. Substance declaration for your information

**Environmental Disclosure** [Product Environmental Profile](#)

**Weee** The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

**Circularity Profile** No need of specific recycling operations