

Product datasheet

Specifications



EasyLogic PM2X30 - I/O Module - Digital - 2 inputs + 2 relay outputs

METSEPM2K2DI2RO

Price: 166.95 USD

Main

Range	PowerLogic
Product Or Component Type	I/O module
Device Application	Optional expansion module
Range Compatibility	EasyLogic EasyLogic PM2100 PM2130 EasyLogic EasyLogic PM2200 PM2230

Complementary

[Ui] Rated Insulation Voltage	2500 V
Number Of Outputs	2 relay
Output Voltage	250 V AC 24 V DC
Number Of Inputs	2 digital
Input Voltage	30 V DC
Width	90.5 mm
Depth	14.6 mm
Height	53 mm
Net Weight	50 g

Environment

Ambient Air Temperature For Operation	-10...60 °C
Ambient Air Temperature For Storage	-25...70 °C

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	4.83 cm
Package 1 Width	8.38 cm
Package 1 Length	9.4 cm
Package 1 Weight	0.12 kg

Excluding VAT, FCA Jabal Ali & are subject to change – check with your local distributor.

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency RoHS/REACH

Well-being performance

Mercury Free

Rohs Exemption Information [Yes](#)

Certifications & Standards

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive Compliant with Exemptions

China Rohs Regulation [China RoHS declaration](#)

Environmental Disclosure [Product Environmental Profile](#)

Circularity Profile [End of Life Information](#)