Product datasheet

Specification





heavy duty PowerLogic PFC Capacitor, 16.9/20.3 kvar - 440 V -50/60Hz

BLRCH169A203B44

Main

Range Of Product	PowerLogic	
Product Or Component Type	Heavy duty capacitor	
Network Frequency	50/60 Hz	
Series Name	HDuty	
Network Harmonic Content	ontent <= 20 %	
Electrical Parameters	16.9 kvar 440 V 50 Hz 20.3 kvar 440 V 60 Hz	
Maximum Permissible Voltage	rmissible Voltage 1.1 x Un (8 hours over 24 hours)	
Continuous Overcurrent Capacity	vercurrent Capacity 1.8 x ln	
Rated Voltage	ed Voltage 440 V AC 50/60 Hz	

Complementary

-		
Dielectric Losses	< 0.2 W/kvar	
Power Losses	< 0.5 W/kVAr	
Capacitance Tolerance	- 5 % to 10 %	
Voltage Test	2.15 x Un AC between terminals for 10 s <= 660 V - 3 kV AC between terminal and container for 10 s >= 660 V - 6 kV AC between terminal and container for 10 s	
Inrush Current	t 250 x ln	
Maximum Switching Operation Per Year	7000	
Service Life In Hours	130000 h	
Dielectric Material	Metallized polypropylene film with Zn/Al alloy, special resistivity & profile, special edge (wave cut)	
Impregnation Material	Non-PCB dry PUR resin Biodegradable	
Type Of Installation	tallation Indoor installation	
Connections - Terminals	ClampTite terminal	
Mounting Mode	Upright/horizontal	
Diameter	116 mm	
Height	242 mm	
et Weight 2.5 kg		

Environment



Standards	IEC 60831-2 IEC 60831-1	
Ip Degree Of Protection	IP20	
Operating Altitude	2000 m	
Temperature Class	D	
Ambient Air Temperature For Operation	-2555 °C	
Relative Humidity	95 %	

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	57.5 cm
Package 1 Width	53.5 cm
Package 1 Length	73.5 cm
Package 1 Weight	2.5 kg

Contractual warranty

Warranty 18 months



Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO2 products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance

②	Reach Free Of Svhc	
②	Toxic Heavy Metal Free	
②	Mercury Free	
⊘	Rohs Exemption Information	Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant EU RoHS Declaration
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins