Product datasheet

Specification





heavy duty PowerLogic PFC Capacitor, 31.5/37.8 kvar - 440V -50/60Hz

BLRCH315A378B44

Main

Range Of Product	PowerLogic	
Product Or Component Type	Heavy duty capacitor	
Network Frequency	50/60 Hz	
Series Name	HDuty	
Network Harmonic Content	ntent <= 20 %	
Electrical Parameters	31.5 kvar 440 V 50 Hz 37.8 kvar 440 V 60 Hz	
Maximum Permissible Voltage	ble Voltage 1.1 x Un (8 hours over 24 hours)	
Continuous Overcurrent Capacity	ercurrent Capacity 1.8 x In	
Rated Voltage	440 V AC 50/60 Hz	

Complementary

Dielectric Losses	osses < 0.2 W/kvar	
Power Losses	< 0.5 W/kVAr	
Capacitance Tolerance	- 5 % to 10 %	
Voltage Test	2.15 x Un AC between terminals for 10 s <= 660 V - 3 kV AC between terminal and container for 10 s >= 660 V - 6 kV AC between terminal and container for 10 s	
Inrush Current	Current 250 x In	
Maximum Switching Operation Per Year	eration 7000	
Service Life In Hours	130000 h	
Dielectric Material	erial Metallized polypropylene film with Zn/Al alloy, special resistivity & profile, special edge (wave cut)	
Impregnation Material	Non-PCB dry PUR resin Biodegradable	
Type Of Installation	nstallation Indoor installation	
Connections - Terminals	ClampTite terminal	
Mounting Mode	le Upright/horizontal	
Diameter	136 mm	
Height	242 mm	
let Weight 3.2 kg		

Environment

Standards	IEC 60831-2 IEC 60831-1	
Ip Degree Of Protection	IP20	
Operating Altitude	2000 m	
Temperature Class	D	
Ambient Air Temperature For Operation	-2555 °C	
Relative Humidity	95 %	

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	28 cm
Package 1 Width	18 cm
Package 1 Length	18 cm
Package 1 Weight	3.8 kg
Unit Type Of Package 2	S04
Number Of Units In Package 2	3
Package 2 Height	30 cm
Package 2 Width	40 cm
Package 2 Length	60 cm
Package 2 Weight	11.52 kg
Unit Type Of Package 3	S06
Number Of Units In Package 3	15
Package 3 Height	73.5 cm
Package 3 Width	60 cm
Package 3 Length	80 cm
Package 3 Weight	70 kg

Contractual warranty

Warranty 18 months



Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance

Ø	Reach Free Of Svhc	
②	Toxic Heavy Metal Free	
Ø	Mercury Free	
⊘	Rohs Exemption Information	Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant EU RoHS Declaration
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins