

# Product datasheet

Specifications



## VIGILOHM ADVANCED 12 CHANNEL FAULT LOCATOR WITH MODBUS - 100-440VAC/ DC

IMDIFL12MC

### Main

Range	Vigilohm
Device Short Name	IFL12MC
Product Or Component Type	Insulation fault locator
Device Application	Marine application Standard environment application
Electrical Circuit Type	Large or highly disturbed network
Electrical Circuit Type	Power circuit Control/command circuit
Earthing System	IT
User Language	Spanish German Italian Russian French Chinese English Portuguese

### Complementary

Network Rated Voltage	0...480 V - AC at 45...440 Hz (device connected to phase) 0...830 V - AC at 45...440 Hz (device connected to neutral) 0...480 V - DC
Number Of Channels	12
Data Recording	Alarm logs
Type Of Measurement	History of alarms Network insulation resistance - measurement range: 200 Ohm...250 kOhm Earth leakage capacitance - measurement range: 0.1...15 $\mu$ F
Local Signalling	Yellow indicator light: insulation fault Yellow flashing indicator light: communication Green/red indicator light: product status Green indicator light: satisfactory insulation Yellow flashing indicator light: transient fault
Threshold Setting	Alarm: 200 Ohm...200 kOhm
Time Delay Range	0...120 min for signalling circuit
Alarm Per Channel	Alarm threshold: settable per feeder
Accuracy	+/- 15 %
Response Time	$\leq$ 5 s
Auxiliary Supply Voltage	100...440 V DC +/- 15 % 100...440 V AC 45...65 Hz +/- 15 %
Power Consumption In Va	26 VA

<b>Power Consumption In W</b>	10 W
<b>Test Function</b>	Auto test at start and every 5h Remote test Manual
<b>Output Contact</b>	1 C/O standard or fail-safe
<b>Breaking Capacity</b>	250 V - AC at 6 A 48 V - DC at 1 A
<b>Communication Port Protocol</b>	Modbus
<b>Communication Port Support</b>	RS485
<b>Display Type</b>	Digital display
<b>Mounting Mode</b>	Flush-mounted Clip-on
<b>Mounting Support</b>	Panel DIN rail
<b>Mounting Position</b>	Vertical Horizontal
<b>Connections - Terminals</b>	Power supply: removable screw terminal block0.2...2.5 mm <sup>2</sup> Output relay: removable screw terminal block0.2...2.5 mm <sup>2</sup> Toroids inputs: removable screw terminal block0.2...1.5 mm <sup>2</sup> Communication: removable screw terminal block0.2...2.5 mm <sup>2</sup> Voltage inputs: removable screw terminal block0.2...2.5 mm <sup>2</sup>
<b>Material</b>	Thermoplastic
<b>Overvoltage Category</b>	III
<b>Net Weight</b>	0.5 kg
<b>Cut-Out Dimensions</b>	92 x 104 mm
<b>Height</b>	110 mm
<b>Width</b>	108 mm
<b>Depth</b>	59 mm

## Environment

<b>Ip Degree Of Protection</b>	Case: IP20 Front face: IP54
<b>Environmental Characteristic</b>	Exposure to damp heat not in service conforming to IEC 60068-2-30 Exposure to damp heat in service conforming to IEC 60068-2-56 Salt mist conforming to IEC 60068-2-52
<b>Operating Altitude</b>	<= 3000 m
<b>Pollution Degree</b>	2
<b>Relative Humidity</b>	5...92 %
<b>Type Of Installation</b>	Indoor
<b>Standards</b>	IEC 60364-4-41 IEC 61010-1 IEC 60364-5-51 IEC 61557-9
<b>Product Certifications</b>	CE DNV-GL EAC UL cULus
<b>Ambient Air Temperature For Operation</b>	-25...55 °C
<b>Ambient Air Temperature For Storage</b>	-40...85 °C

## Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	9.7 cm
Package 1 Width	18.2 cm
Package 1 Length	13.5 cm
Package 1 Weight	550.0 g
Unit Type Of Package 2	S03
Number Of Units In Package 2	8
Package 2 Height	30.0 cm
Package 2 Width	30.0 cm
Package 2 Length	40.0 cm
Package 2 Weight	5.2 kg

## Sustainability

**Green Premium™ label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency RoHS/REACH

## Well-being performance

Mercury Free

RoHS Exemption Information Yes

## Certifications & Standards

Reach Regulation [REACH Declaration](#)

Eu RoHS Directive Compliant with Exemptions

China RoHS Regulation [China RoHS declaration](#)

Environmental Disclosure [Product Environmental Profile](#)

Weee The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Circularity Profile [End of Life Information](#)